



威樂牌 V6

水溶性防滑地台塗料

產品簡介	
適用範圍	網球場、籃球場、運動場、磚石、水泥及混凝土作保護及隔熱塗膜，室內、室外均可使用。
產品介紹	水溶性有色樹脂類產品，具優良彈性、防滑、堅韌、耐侯性及防黴功能。
優點	低氣味；無毒性；防滑；抗紫外線 水溶性、環保；附著力良好。
抗化學性	乾涸後之塗膜可抗碱、清潔劑、煤油、油脂、抗水性。
技術資料	
指觸乾燥	約 2 小時
膜層乾燥	約 12 小時（溫度 30℃ 濕度 80%及濕膜 0.3 毫米計）
完全乾涸	約 24 小時
覆蓋面積	30 - 35 平方呎／1 公升/ 2 層
顏色	白，灰，紅，綠，藍，黃色
濃度	膠狀；不垂流
使用溫度	-5℃ - 70℃
平均加水比例	V6：水 = 3：1
面層	最少兩層；第二層必須待第一層乾涸後才可施工。
表面處理	
施工表面必須良好、平滑，清除所有油污、沙塵及油脂，修補所有裂縫。 注意:如果是新做的英泥沙表面必須待 4 至 6 星期後才可塗上漆油。	
清洗工具：濕膜狀態時，可用清水洗刷工具，如乾涸需用溶劑清潔。	
包裝數據	
4 公升，20 公升	



VELLOC V6

Water Based Non-Slip Acrylic Coloured Coating

Introduction	
Applications	Applicable to both indoor and outdoor on bricks or cement.
Properties	Vellox V-6 Acrylic Coloured Coating a water borne acrylic emulsion coloured mastic.
Advantages	The dry coating is flexible, non-slippery, tough, excellent resistant to fugue growth and weathering.
Chemical resistance	Dry coat - resistant to water, grease, oil, kerosene, salt and detergent.
Technical Data	
Touch Dry	2 hours
Hard Dry	12 hours (30°C at 80% relative humidity 0.3mm wet thickness).
Complete dry	24 hours
Coverage	20 – 25 ft ² / 1 litre
Colour	White, grey, red, green, blue and yellow
Viscosity	Mastic-like, non-flow on vertical wall
Working Temperature	-5°C – 70°C
Average Water Consumption	V6 : water = 3 : 1
Applying	
Surface to be coated shall be free from oil and loose particles. Apply-over any bitumen based black colour roof waterproofing membrane as a heat reflective and protective layer.	
As a non-slip and decorative coating on asphaltic cement, concrete or masonry surface outdoor or indoor.	
Packing	
4 Litres, 20 Litres	

Note: The foregoing information is published as general information only.
The listed properties and performance characteristics are approximate values and are not part of the product specifications.