

PRODUCT DATA SHEET

weberprim moisture sealer

(Formerly known as E.MIX MOISTURE SEALER)

Effective moisture barrier for bathrooms, wet interiors and high water-absorption substrates

PRODUCT

weberprim moisture sealer is a greenish dispersion which is used as a moisture sealing layer before tiling on wall / floor in wet areas like bathroom and kitchen. Suitable substrates include concrete, cement based plaster, lightweight panel and wooden block surface. However, it should not be used as an admixture to mix with cement-based products.

Uses

- Moisture sealing layer before tiling on wall / floor in wet areas like bathroom, wet interiors and high water absorption substrates

Features and Benefits

- Effective moisture barrier for bathrooms and wet interiors and high water absorption substrates

TECHNICAL DATA

Colour	Greenish dispersion
pH value	7 – 9
VOC content	< 10 g/L
Specific gravity	1.04 g/cm ³

Comparison

	Moisture Vapour Transmission Rate (MVTR)*
weberprim moisture sealer	Approx. 3 – 10 g/m ² /day
Alkyds and modified Alkyds	Approx. 100 – 250 g/m ² /day
Styrene – acrylic copolymers	Approx. 1000 g/m ² /day
Styrene – butadiene copolymers	Approx. 1100 – 1900 g/m ² /day
Acrylic copolymers	Approx. 1200 – 2500 g/m ² /day

*The MVTR is based on a film made from the above respective material.

PROCEDURE

Substrate Preparations

The substrate should be clean, dry and free of dust prior to the application of two coats of **weberprim moisture sealer**.

Procedures

Apply the first sealing coat onto the substrate surface with a brush or roller. The second sealing coat should be applied after the first sealing coat gets dried. The drying time for the first coat is about 1 – 2 hours, depending on the substrate and ambient conditions during application. The drying time for the second coat is about 4 hours before receiving tiles. **Weber TILE ADHESIVE** and **TILE GROUT** series products or other polymer modified cementitious tile adhesive is recommended for tiling.

CONSUMPTION

For absorbent surface, the consumption is approx. 0.3 L/m² in two coats; for non-absorbent surface, the consumption is approx. 0.15 L/m² in two coats.

Please refer to our method statement for procedures in details.

STORAGE AND PACKING

weberprim moisture sealer is delivered in 20 L drum. Storage life is 12 months if the product is kept in a dry place. Prevent storage under extreme condition. Stir before use.

HEALTH AND SAFETY

Recommend to wear NOISH approved or equivalent particulate face mask when mixing the material.

Material contains cement, which may produce an allergic effect.

Material may cause irritation to eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical assistance. After contact with skin, wash immediately with plenty of soap and water.

Keep out of reach of children.

Please refer to Material Safety Data Sheet (MSDS) for health, safety and handling of the product.

CLEANING & DISPOSAL OF WASTE

Cured material can be removed mechanically, if uncured, material can be removed with water. Dispose of waste in accordance with legislation.

* Note: The information and physical data in this catalogue is given to the best of our knowledge under standard testing method and controlled environment. The results may vary with different weather / site conditions, workmanship or substrates. This is beyond our control that we shall not be liable for any faults or consequences arising or associated with this. We suggest comprehensive tests to be conducted before final application. Unless specified, all technical data are average values with curing time of 28 days. We reserve the right to update or amend the contents in the light of new findings during the course of research and development.